

Appliances properties: Wodtke GmbH - Levi HK 05 A1

Master data		
Date of entry	Jan 14, 2009	
Manufacturer	Wodtke GmbH	
Model	Levi HK 05 A1	
Nominal heat output [kW]	9	
Continuous burning appliance	_	
Type test standard	DIN 18895	
Year of testing	1997	
Test laboratory	RWE Rheinbraun AG	
Number of test laboratory	4.1	
Number of test report	RB BF1-Hn 14/97	
Flue gas values		

	Wood
Flue gas mass flow [g/s]	19
Flue gas mass flow [g/s]	350
Necessary flue draught [Pa]	12

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm: Inset appliances (with closed firedoor) D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2024 F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor) Evaluation

D - 1.BlmSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information