

Appliances properties: skantherm GmbH & Co. KG - cado (mehrfachbelegbar)

Date of entry Mar 6, 2012 Manufacturer Skantherm GmbH & Co. KG Model Cado (mehrfachbelegbar) Nominal heat output [kW] 8 Continuous burning appliance Type test standard DIN EN 13240 Year of testing 2006 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report Wood Flue gas values Flue gas was flow [g/s] Researcy flue draught [Pa] Further important characteristics of the appliance Suitability for installation to a shared flue¹¹ Connectivity to the central heating system ■ Mar 6, 2012 Santafinerm GmbH & Co. KG Co.			
Manufacturer Model cado (mehrfachbelegbar) Nominal heat output [kW] 8 Continuous burning appliance Type test standard DIN EN 13240 Year of testing 2006 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance Suitability for installation to a shared flue 1) **Continuous burning and (mehrfachbelegbar) 8 **Continuous burning appliance Wood **Wood **Wood **Five gas mass flow [g/s] **Five gas m	Master data		
Model cado (mehrfachbelegbar) Nominal heat output [kW] 8 Continuous burning appliance — Type test standard DIN EN 13240 Year of testing 2006 Test laboratory RRF Rhein-Ruhr-Feuerstattenprüfstelle GmbH Number of test laboratory 2 Number of test report 40 99 107 Flue gas values Wood Flue gas mass flow [g/s] 8 Flue gas mass flow [g/s] 8 Fue gas mass flow [g/s] 10 Further important characteristics of the appliance Further important characteristics of the appliance	Date of entry	Mar 6, 2012	
Nominal heat output [kW] 8 Continuous burning appliance	Manufacturer	skantherm GmbH & Co. KG	
Continuous burning appliance Type test standard DIN EN 13240 Year of testing 2006 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test report 40 99 107 Flue gas values Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance	Model	cado (mehrfachbelegbar)	
Type test standard Year of testing 2006 RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory Number of test report Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾	Nominal heat output [kW]	8	
Year of testing Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Seessary flue draught [Pa] Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾	Continuous burning appliance	_	
Test laboratory Number of test laboratory Number of test report Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Sultability for installation to a shared flue 1) RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Wood Wood Wood Fue gas mass flow [g/s] 8 Flue gas mass flow [g/s] 10 Further important characteristics of the appliance	Type test standard	DIN EN 13240	
Number of test laboratory Number of test report Flue gas values Wood Flue gas mass flow [g/s] Fue gas mass flow [g/s] Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾	Year of testing	2006	
Flue gas values Wood	Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Flue gas values Wood Flue gas mass flow [g/s] 8 Flue gas mass flow [g/s] 361 Necessary flue draught [Pa] 10 Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾	Number of test laboratory	2	
Flue gas mass flow [g/s] 8 Flue gas mass flow [g/s] 361 Necessary flue draught [Pa] 10 Further important characteristics of the appliance Suitability for installation to a shared flue 1)	Number of test report	40 99 107	
Flue gas mass flow [g/s] 361 Necessary flue draught [Pa] 10 Further important characteristics of the appliance Suitability for installation to a shared flue 1)	Flue gas values		
Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance Suitability for installation to a shared flue 1)			Wood
Necessary flue draught [Pa] Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾	Flue gas mass flow [g/s]		8
Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾	Flue gas mass flow [g/s]		361
Suitability for installation to a shared flue ¹⁾	Necessary flue draught [Pa]		10
Suitability for installation to a shared flue ¹⁾			
	Further important characteristics of the appliance		
	Suitability for installation to a shared flue ¹⁾		J
Connectivity to the central heating system			▼
	Connectivity to the central heating system		_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood Norm DIN EN 13240: Roomheater for wood logs Evaluation EU - Regulation (EU) 2015/1185 (Ecodesign) — D - 1.BImSchV ✓ A - Austrian regulation referred to Art 15a B-VG ↓ CH - Swiss clean air act ✓ DK - Danish regulation for air pollution from wood burners — F - Crédit d'impôt à la transition énergétique — I - Italian Decree No. 186 ↓

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing

D - 1.BImSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information