

## Appliances properties: Austroflamm GmbH - KE 45x51 K 2.0

Master data Date of entry Feb 16, 2024 Austroflamm GmbH Manufacturer Model KE 45x51 K 2.0 Nominal heat output [kW] Declared nominal space heating output [kW] Continuous burning appliance **DIN EN 13229** Type test standard Year of testing 2023 Strojirensky Zkusebni Ustav s.p. **Test laboratory** Number of test laboratory

Flue gas values

Number of test report

	Wood
Flue gas mass flow [g/s]	6.1
Flue gas mass flow [g/s]	262
Necessary flue draught [Pa]	10

1015-CPR-30-16564/1/TZ

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

<sup>\*</sup>A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Evaluation of emission data and efficiency Wood

EU-Inset appliance according to EN13229	Evaluation
EU - Regulation (EU) 2015/1185 (Ecodesign)	<b>*</b>
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	<b>*</b>
CH - Swiss clean air act	<b>*</b>
DK - Danish regulation for air pollution from wood burners	<b>*</b>
F - Crédit d'impôt à la transition énergétique	7☆
I - Italian Decree No. 186	南南南

## Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	1



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information